



**Electrical Data:**

Current rating: 2Amps  
 Dielectric Withstanding Voltage: 500VAC for one minute  
 Contact Resistance: < 30 mΩ  
 Insulation Resistance: > 1000 MΩ  
 Operating Temperature: -40°C ~ +105°C

**Construction:**

Insulator: Black Glass Filled Polyester  
 Flammability Rating: UL 94V-0  
 Contacts: Phosphor Bronze of copper alloy  
 Plating: gold  
 Standard: Nylon-6T

**备注:**

- 1、A= 2.00 X No. of Positions + 19.54
- 2、B= 2.00 X No. of Contacts - 2.00
- 3、C= 2.00 X No. of Contacts + 6.5
- 4、D= 2.00 X No. of Contacts + 15.7
- 5、胶壳用常规标准胶壳，2xNo. of Contacts
- 6、材质：PA6T 颜色：黑色
- 7、方针表层镀金
- 8、胶壳材质必须能过回流焊，及回流焊过程中不脱落及融合



Http://www.ciscom.com

深圳市新世联电子有限公司

TEL: +86 (755) 29912370 FAX: 29912372

Tolerance Unless  
 Otherwise Specified

Title

PH2.00 牛角(矮耳扣) SWT

.X ~ ±0.30



Units

Scale

REV NO.

Material No.

.XX ~ ±0.25



mm

2:1

V0

XXXX-XXXX-XX-XX

.XXX ~ ±0.20

Drawing By

Date

Reviewed By

Date

Approval By Date

Angle ~ ± 3°

ChenShan

2023/02/22