

	1	2	3	4	5	6	7	8	9	10	11																																																																							
A	<p>Technical drawing showing front, side, and bottom views of a network socket with dimensions. Front view: 31.1, 13.97, 25.4, 3.2, 0.7. Side view: 21.0, 13.5, 3.3, 2.5, 2.54, 8.89, 4.57, 6.1, 1.3, 0.65. Bottom view: 30.85, 25.4, 13.97, 3-ϕ1.7, 2-ϕ3.25, 1.27, 8.89, 16-ϕ0.9, 4.57, 8.89, 1.27.</p>																																																																																	
B	<p>技术参数 (SPECIFICATION):</p> <p>温度范围 (TEMPERATURE RANGE): -40 ~ +70 °C</p> <p>额定电压 (VOLTAGE RATING): 125V</p> <p>额定电流 (CURRENT RATING): 1.5A</p> <p>接触电阻 (CONTACT RESISTANCE): \leq30mΩ</p> <p>绝缘电阻 (INSULATION RESISTANCE): \geq500MΩ</p> <p>耐压 (DIELECTRIC STRENGTH): 1000V AC / (50HZ) / Min</p> <p>插拔力 (MATING AND UNMATING FORCE): 3 ~ 20N</p> <p>寿命 (DURABILITY): 750 CYCLES MIN</p>																																																																																	
C	<p>材 料 (MATERIAL):</p> <p>基 座 (Housing): GLASS FILLED POLYESTER (UL94V-0)</p> <p>插 针 (CONTACT): PHOSPHOR BRONZE ϕ0.46mm</p> <p>镀 层 (PLATING): GOLD PLATING OVER NICKEL</p> <p>外 壳 (SHIELD): COPPER ALLOY t=0.2mm PLATING NICKEL</p>																																																																																	
D	<p>网络插座外形图</p> <p>PCB LAYOUT (BOTTOM VIEW) RECOMMENDED</p>																																																																																	
E	<p>网络插座外形图</p>																																																																																	
F	<p>网络插座</p>																																																																																	
G	<table border="1"> <tr> <td>一般公差</td> <td>品 名:</td> <td colspan="9">网络插座</td> </tr> <tr> <td>>30~</td> <td>±0.45</td> <td>料 号:</td> <td colspan="9">RJH-59-01-12 (无灯无弹前脚4.57)</td> </tr> <tr> <td>>10~30</td> <td>±0.35</td> <td>型 号:</td> <td colspan="9">RJ45</td> </tr> <tr> <td>~10</td> <td>±0.25</td> <td>图 号:</td> <td colspan="9"></td> </tr> <tr> <td>角 度:</td> <td>±5°</td> <td>单 位:</td> <td>mm</td> <td>比 例:</td> <td>1:1</td> <td>纸 张:</td> <td>A4</td> <td colspan="4"></td> </tr> <tr> <td>页 面:</td> <td>1 of 1</td> <td>版 本:</td> <td colspan="9"></td> </tr> </table>											一般公差	品 名:	网络插座									>30~	±0.45	料 号:	RJH-59-01-12 (无灯无弹前脚4.57)									>10~30	±0.35	型 号:	RJ45									~10	±0.25	图 号:										角 度:	±5°	单 位:	mm	比 例:	1:1	纸 张:	A4					页 面:	1 of 1	版 本:									
一般公差	品 名:	网络插座																																																																																
>30~	±0.45	料 号:	RJH-59-01-12 (无灯无弹前脚4.57)																																																																															
>10~30	±0.35	型 号:	RJ45																																																																															
~10	±0.25	图 号:																																																																																
角 度:	±5°	单 位:	mm	比 例:	1:1	纸 张:	A4																																																																											
页 面:	1 of 1	版 本:																																																																																
A/0	<p>新 出 版 发 行</p>																																																																																	
版 次	<p>变 更 履 历</p>																																																																																	
1	1			2			3																																																																											
<p>请在图上任意处</p>																																																																																		