



DIMENSIONAL & ORDERING INFORMATION	
POLES	2-16POLES
PITCH BETWEEN POLES	2.50MM
VOLTAGE RATING	250V AC, DC
CURRENT RATING	3.0A
WITHSTANDING VOLTAGE	1000V AC/MINUTE
CONTACT RESISTANCE	30mΩ MAX
INSULATION RESISTANCE	1000MΩ MIN
TEMPERATURE RANGE	-25°C ~ +85°C
APPLICABLE WLRE	AWG#28 ~ #22
MATERIAL	NYLON66 UL94V-0

E			Units	mm	Scale	5:1	Drawing By	Date	<b>CISCONN</b> ® 深圳市新世联电子有限公司 Http://www.cisconn.com TEL:+86(755)29912370 FAX:29912372		
D			Tolerance Unless				JOBLIN	2013/09/14	A		
C			Otherwise Specified				Reviewed By	Date	Date	2013/09/14	Title
B				.X	~ ±0.30				Sheet	1 of 1	PH2. 50mm XH-2P胶壳
A	RELEASED	2013/03/16		.XX	~ ±0.25		Approvai By	Date	Third Angle Projection	Drawing No.	REV
REV	ECN.NO.	Date		.XXX	~ ±0.20				F/Name		A
				Angle	~ ± 3°						